

Standard line



Diameter wheel	400	mm
Width wheel	95	mm
Width rim(axle length)	75	mm
Description on tyre	4.80/4.00 - 8	inch(25,4 mm)
Type rim(width x diameter)	2.50A x 8	inch(25,4 mm)
Weight	2200	gram
Recomm. tyre pressure	1,5	bar
Bearings(2RS)	20	mm
Ply-rating	4	pr
Spokes	5	pieces
Material rim	plastic	
Color rim	black/red	
Profile	line	
Distance pipe	yes	
Innertube	no	
Use on hard sand	****	
Use on soft sand	**	
Use on gras	***	
Use on asfalt	***	
Use on grind/rocks	**	
Corrosion resistance	*****	
Average	*	
Eccelent	*****	

Standaard block



Diameter wheel	400	mm
Width wheel	95	mm
Width rim(axle length)	75	mm
Description on tyre	4.80/4.00 - 8	inch(25,4 mm)
Type rim(width x diameter)	2.50A x 8	inch(25,4 mm)
Weight	2600	gram
Recomm. tyre pressure	1,5	bar
Bearings(2RS)	20	mm
Ply-rating	4	pr
Spokes	5	pieces
Material rim	plastic	
Color rim	black/red	
Profile	block	
Distance pipe	yes	
Innertube	yes	
Use on hard sand	****	
Use on soft sand	**	
Use on gras	*****	
Use on asfalt	****	
Use on grind/rocks	***	
Corrosion resistance	*****	
Average	*	
Eccelent	*****	



Slick



Diameter wheel	445	mm
Width wheel	95	mm
Width rim(axle length)	75	mm
Description on tyre	5,00-8	inch(25,4 mm)
Type rim(width x diameter)	2.50A x 8	inch(25,4 mm)
Weight	3900	gram
Recomm. tyre pressure	1,5	bar
Bearings(2RS)	20	mm
Ply-rating	4	pr
Spokes	5	pieces
Material rim	plastic	
Color rim	black/red	
Profile	block	
Distance pipe	yes	
Innertube	yes	
Use on hard sand	****	
Use on soft sand	**	
Use on gras	*	
Use on asfalt	*****	
Use on grind/rocks	****	
Corrosion resistance	*****	
Average	*	
Eccelent	*****	

Standaard F1



Diameter wheel	380	mm
Width wheel	78	mm
Width rim(axle length)	75	mm
Description on tyre	4.80/4.00 - 8	inch(25,4 mm)
Type rim(width x diameter)	2.50A x 8	inch(25,4 mm)
Weight	2500	gram
Recomm. tyre pressure	1,5	bar
Bearings(2RS)	20	mm
Ply-rating	4	pr
Spokes	5	pieces
Material rim	plastic	
Color rim	black/red	
Profile	F1	
Distance pipe	yes	
Innertube	yes	
Use on hard sand	***	
Use on soft sand	*	
Use on gras	*****	
Use on asfalt	****	
Use on grind/rocks	***	
Corrosion resistance	*****	
Average	*	
Eccelent	*****	



Midi F1



Diameter wheel	400	mm
Width wheel	135	mm
Width rim(axle length)	75	mm
Description on tyre	16x6.50 - 8	inch(25,4 mm)
Type rim(width x diameter)	2.50A x 8	inch(25,4 mm)
Weight	3940	gram
Recomm. tyre pressure	1,5	bar
Bearings(2RS)	20	mm
Ply-rating	4	pr
Spokes	5	pieces
Material rim	plastic	
Color rim	black/red	
Profile	F1	
Distance pipe	yes	
Innertube	yes	
Use on hard sand	****	
Use on soft sand	**	
Use on gras	*****	
Use on asfalt	****	
Use on grind/rocks	***	
Corrosion resistance	*****	
Average	*	
Eccelent	*****	

Midi



Diameter wheel	400	mm
Width wheel	140	mm
Width rim(axle length)	75	mm
Description on tyre	16x6.50 - 8	inch(25,4 mm)
Type rim(width x diameter)	2.50A x 8	inch(25,4 mm)
Weight	4500	gram
Recomm. tyre pressure	1,5	bar
Bearings(2RS)	20	mm
Ply-rating	4	pr
Spokes	5	pieces
Material rim	plastic	
Color rim	black/red	
Profile	line	
Distance pipe	yes	
Innertube	yes	
Use on hard sand	****	
Use on soft sand	**	
Use on gras	*****	
Use on asfalt	****	
Use on grind/rocks	***	
Corrosion resistance	*****	
Average	*	
Eccelent	*****	



Midi bigfoot



Diameter wheel	450	mm
Width wheel	180	mm
Width rim(axle length)	75	mm
Description on tyre	18x8,50-8	inch(25,4 mm)
Type rim(width x diameter)	2.50A x 8	inch(25,4 mm)
Weight	5800	gram
Recomm. tyre pressure	1-1,5	bar
Bearings(2RS)	20	mm
Ply-rating	4	pr
Spokes	5	pieces
Material rim	plastic	
Color rim	black/red	
Profile	line	
Distance pipe	yes	
Innertube	yes	
Use on hard sand	****	
Use on soft sand	***	
Use on gras	*****	
Use on asfalt	****	
Use on grind/rocks	***	
Corrosion resistance	*****	
Average	*	
Eccelent	*****	

Midi bigfoot AS



Diameter wheel	430	mm
Width wheel	220	mm
Width rim(axle length)	105	mm
Description on tyre	18x9,50-8	inch(25,4 mm)
Type rim(width x diameter)	8,00x8	inch(25,4 mm)
Weight	6772	gram
Recomm. tyre pressure	1-1,5	bar
Bearings(2RS)	20	mm
Ply-rating	4	pr
Spokes	10	pieces
Material rim	plastic	
Color rim	black	
Profile	line	
Distance pipe	yes	
Innertube	yes	
Use on hard sand	****	
Use on soft sand	****	
Use on gras	*****	
Use on asfalt	****	
Use on grind/rocks	****	
Corrosion resistance	*****	
Average	*	
Eccelent	*****	



Midi bigfoot MDT AS



Diameter wheel	450	mm
Width wheel	240	mm
Width rim(axle length)	105	mm
Description on tyre	18x8,50-8	inch(25,4 mm)
Type rim(width x diameter)	8,00x8	inch(25,4 mm)
Weight	7128	gram
Recomm. tyre pressure	1-1,5	bar
Bearings(2RS)	20	mm
Ply-rating	4	pr
Spokes	10	pieces
Material rim	plastic	
Color rim	black	
Profile	block	
Distance pipe	yes	
Innertube	yes	
Use on hard sand	****	
Use on soft sand	*	
Use on gras	****	
Use on asvalt	****	
Use on grind/rocks	****	
Corrosion resistance	****	
Average	*	
Eccelent	****	

Scorpion light



Diameter wheel	480	mm
Width wheel	190	mm
Width rim(axle length)	75	mm
Description on tyre	18x9,50-8	inch(25,4 mm)
Type rim(width x diameter)	2,50x8	inch(25,4 mm)
Weight	5970	gram
Recomm. tyre pressure	0,4-0,7	bar
Bearings(2RS)	20	mm
Ply-rating	2	pr
Spokes	5	pieces
Material rim	plastic	
Color rim	black/red	
Profile	scorpion	
Distance pipe	yes	
Innertube	yes	
Use on hard sand	**	
Use on soft sand	*	
Use on gras	****	
Use on asvalt	*	
Use on grind/rocks	***	
Corrosion resistance	****	
Average	*	
Eccelent	****	



Scorpion fullsize



Diameter wheel	445	mm
Width wheel	245	mm
Width rim(axle length)	75	mm
Description on tyre	18x9,50-8	inch(25,4 mm)
Type rim(width x diameter)	7,00x8	inch(25,4 mm)
Weight	8254	gram
Recomm. tyre pressure	0,4-0,7	bar
Bearings(2RS)	20	mm
Ply-rating	2	pr
Spokes	5	pieces
Material rim	steel	
Color rim	grey	
Profile	scorpion	
Distance pipe	yes	
Innertube	yes	
Use on hard sand	***	
Use on soft sand	*	
Use on gras	****	
Use on asfalt	*	
Use on grind/rocks	****	
Corrosion resistance	*	
Average	*	
Eccelent	****	

Scorpion fullsize AS



Diameter wheel	570	mm
Width wheel	230	mm
Width rim(axle length)	105	mm
Description on tyre	21x12-8	inch(25,4 mm)
Type rim(width x diameter)	8,00x8	inch(25,4 mm)
Weight	10447	gram
Recomm. tyre pressure	0,4-0,7	bar
Bearings(2RS)	20	mm
Ply-rating	2	pr
Spokes	10	pieces
Material rim	plastic	
Color rim	black	
Profile	scorpion	
Distance pipe	yes	
Innertube	yes	
Use on hard sand	***	
Use on soft sand	*	
Use on gras	*****	
Use on asfalt	*	
Use on grind/rocks	*****	
Corrosion resistance	*****	
Average	*	
Eccelent	*****	



Bigfoot light



Diameter wheel	540	mm
Width wheel	200	mm
Width rim(axle length)	75	mm
Description on tyre	21x12-8	inch(25,4 mm)
Type rim(width x diameter)	2,50x8	inch(25,4 mm)
Weight	5500	gram
Recomm. tyre pressure	0,4-0,7	bar
Bearings(2RS)	20	mm
Ply-rating	2	pr
Spokes	5	pieces
Material rim	plastic	
Color rim	black	
Profile	slick	
Distance pipe	yes	
Innertube	on request	
Use on hard sand	****	
Use on soft sand	****	
Use on gras	**	
Use on asfalt	**	
Use on grind/rocks	*	
Corrosion resistance	*****	
Average	*	
Eccelent	*****	

Bigfoot full



Diameter wheel	545	mm
Width wheel	245	mm
Width rim(axle length)	90	mm
Description on tyre	21x12-8	inch(25,4 mm)
Type rim(width x diameter)	7,00x8	inch(25,4 mm)
Weight	8214	gram
Recomm. tyre pressure	0,4-0,7	bar
Bearings(2RS)	20	mm
Ply-rating	2	pr
Spokes	0	pieces
Material rim	steel	
Color rim	grey	
Profile	slick	
Distance pipe	yes	
Innertube	on request	
Use on hard sand	****	
Use on soft sand	*****	
Use on gras	**	
Use on asfalt	**	
Use on grind/rocks	*	
Corrosion resistance	*	
Average	*	
Eccelent	*****	



Fullsize AS



Diameter wheel	530	mm
Width wheel	255	mm
Width rim(axle length)	105	mm
Description on tyre	21x12-8	inch(25,4 mm)
Type rim(width x diameter)	8,00x8	inch(25,4 mm)
Weight	6502	gram
Recomm. tyre pressure	0,4-0,7	bar
Bearings(2RS)	20	mm
Ply-rating	2	pr
Spokes	10	pieces
Material rim	plastic	
Color rim	black	
Profile	slick	
Distance pipe	yes	
Innertube	no	
Use on hard sand	****	
Use on soft sand	*****	
Use on gras	**	
Use on asfalt	*	
Use on grind/rocks	**	
Corrosion resistance	*****	
Average	*	
Eccelent	*****	

Fullsize Cadkat



Diameter wheel	545	mm
Width wheel	245	mm
Width rim(axle length)	90	mm
Description on tyre	21x12-8	inch(25,4 mm)
Type rim(width x diameter)	7,00x8	inch(25,4 mm)
Weight	6040	gram
Recomm. tyre pressure	0,4-0,7	bar
Bearings(2RS)	20	mm
Ply-rating	2	pr
Spokes	10	pieces
Material rim	plastic	
Color rim	red/black	
Profile	slick	
Distance pipe	yes	
Innertube	no	
Use on hard sand	****	
Use on soft sand	*****	
Use on gras	**	
Use on asfalt	*	
Use on grind/rocks	**	
Corrosion resistance	*****	
Average	*	
Eccelent	*****	



Discwheel



buggywielen.nl

Diameter wheel	560	mm
Width wheel	80	mm
Width rim(axle length)	90	mm
Description on tyre	-	inch(25,4 mm)
Type rim(width x diameter)	16	inch(25,4 mm)
Weight	6800	gram
Recomm. tyre pressure	0,4-0,7	bar
Bearings(2RS)	20	mm
Ply-rating	4	pr
Spokes	0	pieces
Material rim	steel	
Color rim	grey	
Profile	line/block	
Distance pipe	yes	
Innertube	on request	
Use on hard sand	****	
Use on soft sand	*	
Use on gras	**	
Use on asvalt	*****	
Use on grind/rocks	**	
Corrosion resistance	*	
Average	*	
Eccelent	*****	

Moutainboard 228



buggywielen.nl

Diameter wheel	228	mm
Width wheel	64	mm
Width rim(axle length)	75	mm
Description on tyre	3,00x4	inch(25,4 mm)
Type rim(width x diameter)	2,10x4	inch(25,4 mm)
Weight	1800	gram
Recomm. tyre pressure	1,5	bar
Bearings(2RS)	20	mm
Ply-rating	4	pr
Spokes	0	pieces
Material rim	plastic	
Color rim	red	
Profile	line	
Distance pipe	no	
Innertube	yes	
Use on hard sand	****	
Use on soft sand	**	
Use on gras	***	
Use on asvalt	***	
Use on grind/rocks	**	
Corrosion resistance	*****	
Average	*	
Eccelent	*****	



Mountainboard 265 block



Diameter wheel	265	mm
Width wheel	85	mm
Width rim(axle length)	75	mm
Description on tyre	3,00x4	inch(25,4 mm)
Type rim(width x diameter)	2,10x4	inch(25,4 mm)
Weight	1900	gram
Recomm. tyre pressure	1,5	bar
Bearings(2RS)	20	mm
Ply-rating	4	pr
Spokes	0	pieces
Material rim	plastic	
Color rim	red	
Profile	block	
Distance pipe	no	
Innertube	yes	
Use on hard sand	***	
Use on soft sand	**	
Use on gras	****	
Use on asfalt	***	
Use on grind/rocks	**	
Corrosion resistance	*****	
Average	*	
Excellent	*****	

Mountainboard 265 line



Diameter wheel	265	mm
Width wheel	85	mm
Width rim(axle length)	75	mm
Description on tyre	3,00x4	inch(25,4 mm)
Type rim(width x diameter)	2,10x4	inch(25,4 mm)
Weight	1900	gram
Recomm. tyre pressure	1,5	bar
Bearings(2RS)	20	mm
Ply-rating	4	pr
Spokes	0	pieces
Material rim	plastic	
Color rim	red	
Profile	line	
Distance pipe	no	
Innertube	yes	
Use on hard sand	***	
Use on soft sand	**	
Use on gras	****	
Use on asfalt	***	
Use on grind/rocks	**	
Corrosion resistance	*****	
Average	*	
Excellent	*****	



Mountainboard 300



Diameter wheel	300	mm
Width wheel	100	mm
Width rim(axle length)	75	mm
Description on tyre	3,00x4	inch(25,4 mm)
Type rim(width x diameter)	2,10x4	inch(25,4 mm)
Weight	2100	gram
Recomm. tyre pressure	1,5	bar
Bearings(2RS)	20	mm
Ply-rating	4	pr
Spokes	0	pieces
Material rim	plastic	
Color rim	red	
Profile	block	
Distance pipe	no	
Innertube	yes	
Use on hard sand	****	
Use on soft sand	***	
Use on gras	****	
Use on asvalt	****	
Use on grind/rocks	***	
Corrosion resistance	*****	
Average	*	
Eccelent	*****	

© buggywheels.com



Bearings



Description	Dimensions bearing in mm	Axle length in mm	Mat. Rim	Type bearing
ballhead	10x30	ligt aan type buggy	steel/RVS	<b>6200 2RS</b>
standard rim	12x32	76	plastic	<b>6201 2RS</b>
standard rim	15x32	76	plastic	<b>6002 2RS</b>
cadkat bigfoot rim	20x42	90	plastic	<b>6004 2RS</b>
standard rim	20x47	75	plastic	<b>6204 2RS</b>
Discwheel	20x47	90	steel	<b>6204 2RS</b>
Bigfoot rim	20x47	75	steel	<b>6204 2RS</b>
AS rim	20x52	105	plastic	<b>6304 2RS</b>